

CN55185-M1

## IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT (IECEE) CB SCHEME

## **CB TEST CERTIFICATE**

**Product** 

Pushbutton

Name and address of the applicant

Siemens Electrical Apparatus Ltd., Suzhou No.455 Zhujiang Road, New District, Suzhou, Jiangsu

Province, P.R.China

Name and address of the manufacturer

Siemens Electrical Apparatus Ltd., Suzhou No.455 Zhujiang Road, New District, Suzhou, Jiangsu

Province, P.R.China

Name and address of the factory

Note: When more than one factory, please report on page 2

Siemens Electrical Apparatus Ltd., Suzhou, Tiantai Branch

No.699-10, Jigong Road, Tiantai County, Zhejiang

Province, P.R. China

Ratings and principal characteristics

See the Appendix

Trademark / Brand (if any)

APT

Customer's Testing Facility (CTF) Stage used

N/A

Model / Type Ref.

LA39

Additional information (if necessary may also be reported on page 2)

Original CB certificate No. is CN55185, dated 2021-11-22. The M1 certificate has been issued to change parameters.

A sample of the product was tested and found to be in conformity with

IEC 60947-5-1:2016(4th Edition)

As shown in the Test Report Ref. No. which forms part of this Certificate


00901-CB2021CQC-097094-M1

This CB Test Certificate is issued by the National Certification Body

## CHINA QUALITY CERTIFICATION CENTRE

Section 9, No. 188 Nansihuan Xilu, Beijing 100070 P. R. China Tel: +86-10-83886666 Fax: +86-10-83886282 website: http://www.cqc.com.cn

Date: Nov.07,2023









CN55185-M1

LA39

Ui:660V;Uimp:4kV;Ith:10A;

Momentary action: AC-15: Ue/Ie: AC660V/0.8A, AC380V/1.5A, AC220V/2.5A,

AC110V/5A,AC48V/10A,AC24V/10A;

DC-13:Ue/le:DC24V/3.6A,DC48V/1.8A,DC110V/0.8A,

DC220V/0.4A,DC440V/0.2A;

Squirm action:AC-15:Ue/le:AC660V/2A,AC380V/4A,AC220V/6A,

AC110V/10A,AC48V/10A,AC24V/10A;

DC-13:Ue/le:DC24V/6A,DC48V/3A,DC110V/1A,DC220V/0.5A,

DC440V/0.25A;

Type A head:except A3,A4,A5 selector switch,ZY(key release E-stop),ZL(pull to release E-stop),

Y/YS(key switch), TCY(push operation key switch) FX XFX CXFX XSFX CXSF: IP40; Other s(general pushbutton, D, T, TD, M, MT, MD, MTD, Z, A1A2 selector switch, Z9, ZC, MR, R, RD): IP54;

Type B head: IP40(General button, D, T, TD, M, MT, MD, MTD, X, XS, CX, CXS, Z can order IP65); Ф22mm.

Page 1 of 1

Additional information (if necessary)

Date: Nov.07,2023 Signature:

Xie ZhaoXu

Tel: +86-10-83886666 Fax: +86-10-83886282